

DESIGNED
& BUILT
IN THE U.S.A.



NOW CARBON



U S YACHTS

USyachts.com



Antrim 25



NOTE: Ultimate 24 Pictured in above photos.



Standard Features

- 800 Lb. carbon fiber retractable foil and lead bulb keel
- Cabin window
- Cockpit storage / outboard motor box with Lewmar Hatch
- Deck-mounted spinnaker pole (articulating pole optional)
- Large self-bailing cockpit
- Non-skid deck surfaces
- Ramp launchable
- Single lifting point for easy hoisting
- Unique structural interior quadrants

Standard Equipment

- 5:1 mainsheet purchase
- Adjustable forestay and rig tensioner
- Bow eye
- Carbon fiber mast and boom
- Cockpit sheet tail bags
- Custom stainless steel bow pulpit,
- Stanchions and lifelines
- Dual purpose hideaway drop board 1 step
- Harken roller furling system
- Lewmar foredeck hatch
- Outboard motor bracket
- Removable carbon fiber rudder
- Running rigging, sheets, and control lines
- Schaefer jib tracks and cars
- Storage lockers with access hatches
- Spinlock rope clutches
- Spinlock telescoping tiller extension
- Vangmaster pneumatic rigid vang
- Interior electrical panel, dome lights, gel battery, solar panel and regulator

Standard Accessories

- Spreader boots
- Storage basket

Factory Installed Options

- Accessory bag kit (rudder bag, job sock)
- Class sails (choice of loft)
- Single axle galvanized trailer and Bearing Buddys
- GelCoat waterline stripe (single or double)
- Boat/name graphics
- Lifting strap

Construction

The Antrim 25 is designed by Jim Antrim and built to strict one-design standards. All parts are hand laid, cored (balsa and foam) and vacuum bagged for consistent light weight without sacrificing strength and rigidity. Unidirectional carbon fiber is used throughout. Kevlar is added to the hull for additional strength and offshore sailing. The Antrim 25 is designed with a unique structural interior quadrant system that eliminates the need for space-compromising bulkheads.

Dimensions

LOA24 ft. 5 in.
LWL21 ft. 2 in.
Beam8 ft. 6 in.
Draft (keel up)2 ft. 11 in.
Draft (keel down)5 ft. 6 in.
Displacement2,040 lbs.
Ballast750 lbs.
Mainsail230 sq. ft.
Jib125 sq. ft.
Spinnaker558 sq. ft.
Displ / Length96
Sail Area / Displ.35
Bowsprit5 ft. 8 in.
Displ / Length Ratio96%
Sail Area / Displ Ratio35.30%
J7 ft. 3 in.
I28 ft. 6 in.
P31 ft.
E11 ft. 5 in.
Auxiliary5 bp
Sleeps4
DesignerJim Antrim

Deck Plan & Accommodations

