

DESIGNED
& BUILT
IN THE U.S.A.



U S YACHTS

USyachts.com



Ultimate 20



Standard Features

- 450 Lb. Carbon Fiber Retractable Keel/foil
- Patented Keel Lifting System (#5-431-121)
- Retractable Carbon Deck-mounted Sprit
- Integrated Interior Pan And V-berth With Access Ports
- Integrated Flotation Tanks-interior Berths
- Lexan Locking Hatch And Star-board Drop Board
- Anodized Aluminum Parts
- Safety Skit Non-skid Deck Surfaces
- Ergonomic Design Self Bailing Cockpit
- Single Point Hoist Location
- Cockpit Storage Locker
- Safety-lock Keel Assembly
- Patented Keel Lifting System

Standard Equipment

- Tapered Mast And Stainless Rigging (Carbon Optional)
- Adjustable Jib Halyard
- Single Reef Main Halyard
- Harken Blocks And Cleats
- Harken Heavy Duty Jib Furler
- Harken Spinnaker Turning Blocks And Ratchets
- Internal Sail Controls
- Removable Carbon Fiber Reinforced Rudder
- All Running Rigging, Sheets And Control Lines
- Harken Jib Tracks And Cars
- Tiller Extension
- Interior Storage Gear Baskets (2)
- Bow Eye
- Dual Hinging Mast Step
- Interior Floor Boards, Composite
- Fiberglass Keel Boot
- Painted Trailer

Factory Installed Options

- Stainless Cockpit Stanchions And Life Lines (15 in.)
- Optional Solid Side Bars
- Bow Pulpit
- Motor Compartment Upgrade with Lid And Lock
- Removable Cockpit Sheet Bags (2)
- Removable Outboard Motor Bracket
- Removable Mast Crutch
- Ronstan Calibrated Shroud Adjusters
- Two-tone Deck
- Colored Waterline Stripe
- Cabin Windows
- Racing Line Package Upgrade
- Electronics

Optional Accessories

- Boat Cover
- Rudder Bag
- Jib Sock/ Zippered
- Lifting Strap With Single Attachment Shackle
- Kick Up Rudder
- Life Line Cushions
- Interior V-birth Cushions
- Shallow Water Rudder



Construction

The Ultimate 20 is built to strict one-design standards. All parts are hand laid, cored (balsa and foam) and vacuum bagged utilizing resin infusion for consistent light weight without sacrificing strength and rigidity. Unidirectional carbon fiber reinforcements are used at critical load points.

Dimensions

LOA20 ft. 10 in.
LWL18 ft.
Beam8 ft. 4 in.
Draft (keel up)10 in.
Draft (keel down)5 ft.
Displacement1,260 lbs.
Ballast450 lbs.
Mainsail205 sq. ft.
Jib100 sq. ft.
Class Spinnaker452 sq. ft.
PHRF Max.485 sq. ft.
Bowsprit6 ft.
Displ / Length Ratio84%
Ballast / Displ41%
Sail Area / Displ Ratio46.4%
J7 ft.
I28.08 ft.
P27.60 ft.
E10 ft. 3 in.
DesignerAntrim Design Team

Deck Plan

